


## Three-Terminal Voltage Regulator

### 78L05

#### ■ Features

- Maximum output current: $I_{OM}=0.1A$ .
- Output voltage: $V_O=5V$ .
- Continuous total dissipation: $P_D: 0.5 W$




#### ■ Absolute Maximum Ratings $T_a = 25^\circ C$

Parameter	Symbol	Rating	Unit
Input Voltage	$V_I$	30	V
Operating junction temperature range	$T_{OPR}$	-55 to +125	°C
Storage Temperature Range	$T_{STG}$	-55 to +150	°C

#### ■ Electrical Characteristics ( $V_I=10V, I_O=40mA, 0^\circ C < T_j < 125^\circ C, C_1=0.33 \mu F, C_0=0.1 \mu F$ , unless otherwise specified)


Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Output voltage	$V_O$	$T_j=25^\circ C$	4.8	5.0	5.2	V
		$7V \leq V_I \leq 20V, I_O=1mA-40mA$	4.75	5.0	5.25	V
		$I_O=1mA-70mA$	4.75	5.0	5.25	V
Load regulation	$\Delta V_O$	$T_j=25^\circ C, I_O=1mA-100mA$		15	60	mV
		$T_j=25^\circ C, I_O=1mA-40mA$		8	30	mV
Line regulation	$\Delta V_O$	$7V \leq V_I \leq 20V, T_j=25^\circ C$		32	150	mV
		$8V \leq V_I \leq 20V, T_j=25^\circ C$		26	100	mV
Quiescent current	$I_Q$	$T_j=25^\circ C$		3.8	6	mA
Quiescent current change	$\Delta I_Q$	$0^\circ C < T_j < 125^\circ C, 8V \leq V_I \leq 20V$			1.5	mA
	$\Delta I_Q$	$0^\circ C < T_j < 125^\circ C, 1mA \leq I_O \leq 40mA$			0.1	mA
Output noise voltage	$V_N$	$10Hz \leq f \leq 100KHz$		42		uV
Ripple rejection	$RR$	$8V \leq V_I \leq 20V, f=120Hz, T_j=25^\circ C$	41	49		dB
Dropout voltage	$V_d$	$T_j=25^\circ C$			1.7	V

#### ■ Typical application.




## 78L05


## ■ Typical Characteristics




Output Characteristics




Load Characteristics




Thermal Shutdown



Short Circuit Output Current



Quiescent Current vs Input Voltage



Power Dissipation vs. Ambient Temperature