


Three-Terminal Positive Voltage Regulator

LM78L05



■ Features

- Maximum Output current I_o : 0.1A
- Output Voltage V_o : 5V
- Continuous Total Dissipation P_D : 0.5W ($T_a = 25^\circ\text{C}$)


■ Absolute Maximum Ratings (Operating temperature range applies unless otherwise specified)

Parameter	Symbol	Rating	Unit
Input Voltage	V_I	30	V
Operating Junction Temperature Range	T_{OPR}	-55 ~ +125	°C
Storage Temperature Range	T_{STG}	-55 ~ +150	°C

■ Electrical Characteristics ($V_I=10\text{V}$, $I_o=40\text{mA}$, $C_I=0.33\text{ }\mu\text{F}$, $C_O=0.1\text{ }\mu\text{F}$, unless otherwise specified)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Output Voltage	V_o	$T_J = 25^\circ\text{C}$	4.8	5.0	5.2	V
		$T_J = 0 \sim 125^\circ\text{C}$, $7\text{V} \leq V_I \leq 20\text{V}$, $I_o=1\text{mA} \sim 40\text{mA}$	4.75	5.0	5.25	V
		$T_J = 0 \sim 125^\circ\text{C}$, $I_o=1\text{mA} \sim 70\text{mA}$	4.75	5.0	5.25	V
Load Regulation	ΔV_o	$T_J = 25^\circ\text{C}$, $I_o=1\text{mA} \sim 100\text{mA}$	15	60	60	mV
		$T_J = 25^\circ\text{C}$, $I_o=1\text{mA} \sim 40\text{mA}$	8	30	30	mV
Line Regulation	ΔV_o	$7\text{V} \leq V_I \leq 20\text{V}$	32	150	150	mV
		$T_J = 25^\circ\text{C}$, $8\text{V} \leq V_I \leq 20\text{V}$	26	100	100	mV
Quiescent Current	I_Q	$T_J = 25^\circ\text{C}$	3.8	6	6	mA
Quiescent current Change	ΔI_Q	$T_J = 0 \sim 125^\circ\text{C}$, $8\text{V} \leq V_I \leq 20\text{V}$			1.5	mA
		$T_J = 0 \sim 125^\circ\text{C}$, $1\text{mA} \leq I_o \leq 40\text{mA}$			0.1	
Output Noise Voltage	V_N	$T_J = 25^\circ\text{C}$, $10\text{Hz} \leq f \leq 100\text{KHz}$	42			μV
Ripple Rejection	RR	$T_J = 0 \sim 125^\circ\text{C}$, $8\text{V} \leq V_I \leq 20\text{V}$, $f = 120\text{Hz}$	41	49		dB
Dropout Voltage	V_D	$T_J = 25^\circ\text{C}$			1.7	V

■ Typical Application



Note: Bypass capacitors are recommended for optimum stability and transient response and should be located as close as possible to the regulators.

LM78L05

■ Typical Characteristics

